The Hamk XHD provides maximum power with the twin capacitor AC motor and Hovk's ruggedly reliable floor machine size. 100% nover decision to the flower's of remble pervice. The XHD is powered by the 16 His moor as Wolfered with a wide range of tools, casse less and options weights. The optional DX particle ands the Color solution tank a stom fit splash guard and premain pad driver.

Power

1.5 HP, 66 frame, dual capacitor AC motor
115V, 60 Hz Power. (230V optional).
50 ft. (12-3) SJTOW industrial cord w/ molded plug (HD (Extra Heavy Duty) triple-planetary 11:1 helical-cut lustrial gears, case hardened with weel oupler. Drives Frushes of

lustrial gears, case ha d pads at 175 RPM gineered Design II steel, welded, powe

Il steel, welded, powder-coated tame)ne piece heavy-duty chromed steel handle with variab sition positive handle lock and you dipped foam grrips 3", 15", 17" and 20" chromed steel or brush covers with aparound bumper. Dual steel

Negative pressure on/off swit

Thumb-operated safety switc

1" x 5" non-marking ball hearing whee 部分に efety Features

t 66 dB operation. N分けることが可能ですements. ハンドルは段階調整

CUL listed ed Steel

& Handle er to Drive w Floor

ubbing, (

Lubricated Triple
Planetary Gears

| | MIGHTY15 | MIGHTY17 |
|--------------|--------------|--------------|
| サイズ | 15インチ | 17インチ |
| Speed | 165RPM | 165RPM |
| Motor | 1.0HP | 1.0HP |
| Power Source | 115V 50/60Hz | 115V 50/60Hz |
| Power Cord | 15メートル | 15メートル |
| Amp Draw | 6Amp | 7Amp |
| Weight | 40.0キロ | 40.8キロ |



プレミアムダブルフック パッドドライバー



スプラッシュガード



※ オプション部品



約9キロのフレームウエイト約11キロの馬蹄型ウエイト



株式会社アピコ

〒501-6004 岐阜県羽島郡岐南町野中 6-99 tel 058-248-0635 fax 058-240-5879 〒146-0082 東京都大田区池上 3 丁目 38-12 tel 03-5747-6092

www.apico-pd.jp info@apico-pd.com